

RF Test Report

Report No.: AGC05443240513ER02

PRODUCT DESIGNATION: Magnetic Wireless charger

BRAND NAME : N/A

MODEL NAME : MO2389

APPLICANT: MID OCEAN BRANDS B.V

DATE OF ISSUE : Jun. 07, 2024

STANDARD(S) : ETSI EN 303 417 V1.1.1(2017-09)

REPORT VERSION: V1.0

Attestation of Global Coloniance (Shenzhen) Co., Ltd.



Page 2 of 31

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	1	Jun. 07, 2024	Valid	Initial Release



Report No.: AGC05443240513ER02 Page 3 of 31

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	4
2. EUT DESCRIPTION	
3. DESCRIPTION OF TEST ITEMS	
4. TEST FACILITY	6
5. ETSI EN 303 417 REQUIREMENT	7
5.1 TRANSMITTER H-FIELD REQUIREMENTS	7
5.2 OPERATING FREQUENCY RANGES	12
5.3 TRANSMITTER OUT OF BAND (OOB) EMISSIONS	15
5.4 TRANSMITTER SPURIOUS EMISSIONS	
5.5 RECEIVER BLOCKING	
6. INTERPRETATION OF MEASUREMENT RESULTS	29
APPENDIX I: PHOTOGRAPHS OF TEST SETUP	30
APPENDIX II: PHOTOGRAPHS OF THE FUT	31



Report No.: AGC05443240513ER02 Page 4 of 31

1. TEST RESULT CERTIFICATION

MID OCEAN BRANDS B.V		
Unit 201 2/F,.Laford Centre, 838 Lai Chi Kok Road, Cheung Sha Wan, Kowloon, Hongkong		
MID OCEAN BRANDS B.V		
Unit 201 2/F,.Laford Centre, 838 Lai Chi Kok Road, Cheung Sha Wan, Kowloon, Hongkong		
MID OCEAN BRANDS B.V		
Unit 201 2/F,.Laford Centre, 838 Lai Chi Kok Road, Cheung Sha Wan, Kowloon, Hongkong		
Magnetic Wireless charger		
N/A		
MO2389		
N/A		
N/A		
May 14, 2024		
May 14, 2024 to Jun. 06, 2024		
None		
Normal		
Pass		
AGCRT-EC-RF		

Note: The test results of this report relate only to the tested sample identified in this report.

Reviewed By

Cici Li
(Project Engineer)

Calvin Liu
(Reviewer)

Max Zhang
Authorized Officer

Jun. 07, 2024

Jun. 07, 2024



Page 5 of 31

2. EUT DESCRIPTION

Details of technical specification refer to the description in follows:

Hardware Version	V1.0
Software Version	V1.0
Operate Frequency	100KHz-205KHz
Modulation Type	ASK
ocw	Energy transmission: Low channel 0.961KHz, Middle Channel 0.966KHz, High channel 0.964KHz Data communication: 0.889KHz
Test Channels	Energy transmission: Low channel 128.6KHz, Middle Channel 128.9KHz, High channel 133.8KHz Data communication: 127.8KHz
Antenna Type	Coil Antenna
Operational Mode	Mode 1: base station in stand-by, idle mode Mode 3: communication Mode 4: energy transmission
EUT Input& Output Rating	Input: DC 5V/2A, 9V/1.67V, 12V/1.5A Output: DC 5V/1A, 9V/1.1A, 9V/1.67A
Wireless Charging Output Power	5W/10W/15W (Max 15W)

NOTE: 1. For more information, please refer to User's Manual.

- 2. During the initial establishment of the charging mode (mode 2), no or very low emission occur (below the sensitivity level of the test set-up), so the mode 2 can be assumed as irrelevant for the test.
- 3. Mode 3 and mode 4 have been performed within one set-up, worst-case alignment. But each mode have been tested separately with specific test software.
- 4. The maximum temperature of 40 is not a standard requirement and is measured according to the maximum service temperature stated by the manufacturer.
 - 5. The communication frequency 127.8kHz corresponds to the maximum field strength.



Page 6 of 31

3. DESCRIPTION OF TEST ITEMS

Harmonised Standard ETSI EN 303 417				
	Requirement	Requirement Conditionality		
No	Description			
1	Permitted range of operating frequencies	⊠ Applicable □ Not Applicable		
2	Operating frequency ranges	⊠ Applicable □ Not Applicable		
3	H-field requirements	⊠ Applicable □ Not Applicable		
4	Transmitter spurious emissions	⊠ Applicable □ Not Applicable		
5	Transmitter out of band (OOB) emissions	⊠ Applicable □ Not Applicable		
6	WPT system unwanted conducted emissions	☐ Applicable ⊠ Not Applicable		
7	Receiver blocking	⊠ Applicable □ Not Applicable		

4. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd	
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China	



Page 7 of 31


5. ETSI EN 303 417 REQUIREMENT

5.1 TRANSMITTER H-FIELD REQUIREMENTS

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Feb. 01, 2024	Jan. 31, 2025
Power amplifier	AR	75A250	18464	N/A	N/A
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 05, 2024	Mar. 04, 2026

TEST SETUP:





Page 8 of 31

TEST LIMITS:

The H-field limit in $dB\mu A/m$ at 3 m, H_{3m} , is determined by the following equation:

$$H_{3m} = H_{10m} + C_3 (F.2)$$

Where:H_{10m} is the H-field limit in dBµA/m at 10 m distance according to the present document; andC₃ is a conversion factor in dB determined from figure F.2.

According to EN 303 417 Tablet 3,

Table 3: H-field limits

Frequency range [MHz]	H-field strength limit [dBµA/m at 10 m]	Comments
0,019 ≤ f < 0,021	72	
0,059 ≤ f < 0,061	69,1 descending 10 dB/dec above 0,059 MHz	See note 1
0,079 ≤ f < 0,090	67,8 descending 10 dB/dec above 0,079 MHz	See note 2
0,100 ≤ f < 0,119	42	
0,119 ≤ f < 0,135	66 descending 10 dB/dec above 0,119 MHz	See note 1
0,135 ≤ f < 0,140	42	
0,140 ≤ f < 0,1485	37,7	
0,1485 ≤ f < 0,30	-5	
6,765 ≤ f < 6,795	42	

NOTE 1: Limit is 42 dBµA/m for the following spot frequencies: 60 kHz ± 250 Hz and 129,1 kHz ± 500 Hz.
NOTE 2: At the time of preparation of the present document the feasibility of increased limits for high power wireless power transmission systems to charge vehicles [i.4] was prepared. New specific requirements for such systems (e.g. higher H-field emission limits in the 79 - 90 kHz band) will be reflected within a future revision of the present document.

Correction factor, C3, for limits at 3 m distance, dB




Figure F.2: Conversion factor C₃ versus frequency



Report No.: AGC05443240513ER02 Page 9 of 31

TEST PROCEDURE:

The EUT was placed on the top of an insulating table 0.8 meters above the ground at a semi-anechoic chamber.

The table was rotated 360 degrees to determine the position of the highest radiation.

The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

The H-field is measured with a shielded loop antenna connected to a measurement receiver.

The measuring bandwidth and detector type of the measurement receiver shall be in accordance with EN 300 330 V2.1.1 Table 11.

The EUT operate with modulation under normal and extreme conditions.

TEST RESULTS:

Test Mode: Mode 1

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25℃	5.0	Worst case
TL/VL	0℃	4.5	
TH/VL	40℃	4.5	
TL/VH	0℃	5.5	
TH/VH	40℃	5.5	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1246	23.53	-5.69	17.84	97.00

Test results calculated to 10m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1246	23.53	-36.89	-13.36	65.80



Page 10 of 31

Test Mode: Mode 3

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25℃	5.0	Worst case
TL/VL	-10°C	4.5	
TH/VL	45℃	4.5	
TL/VH	-10℃	5.5	
TH/VH	45℃	5.5	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1278	23.53	5.67	29.20	96.89

Test results calculated to 10m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1278	23.53	-14.63	8.90	65.69



Page 11 of 31

Test Mode: Mode 4

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25℃	5.0	Worst case
TL/VL	-10°C	4.5	
TH/VL	45℃	4.5	
TL/VH	-10 ℃	5.5	
TH/VH	45℃	5.5	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1286	23.53	4.12	27.65	96.85
0.1289	23.53	-7.21	16.32	96.85
0.1338	23.53	-7.69	15.84	96.85

Test results calculated to 10m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1286	23.53	-27.08	-3.55	65.65
0.1289	23.53	-38.41	-14.88	65.65
0.1338	23.53	-38.89	-15.36	65.65

Remark:

(1) Corrected Level (dBuA/m) = Reading Level + Antenna Factor

(2) For the calculated method, please refer to Annex F at EN 300330.

(3) All extreme conditions were considered for test, but only record the worst case.




Page 12 of 31

5.2 OPERATING FREQUENCY RANGES

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Feb. 01, 2024	Jan. 31, 2025
Power amplifer	AR	75A250	18464	N/A	N/A
Active loop antenna(9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 05, 2024	Mar. 04, 2026

TEST SETUP:



TEST PROCEDURE:

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by normal signal,
- 3).Set SPA Center Frequency = fundamental frequency, RBW=VBW=200Hz, Span=5kHz, Detector=RMS. The 99 % OBW function shall be used to determine the operating frequency range, fH is the frequency of the upper marker resulting from the OFR, fL is the frequency of the lower marker resulting from the OFR.
- 4), Both normal test condition and extreme test condition applied

LIMITS

The operating frequency range for emissions shall be within one of the following limits: 19 - 21 kHz, 59 - 61 kHz, 79 - 90 kHz, 100 - 300 kHz, 6 765 - 6 795 kHz.



Page 13 of 31

TEST RESULT

Test Mode: Mode 1

Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Lowest Frequency(K Hz)	Highest Frequency (KHz)	Limit
0℃	5.0	124.161	125.042	100kHz≤&≤300kHz
00	4.5	124.160	125.043	100kHz≤&≤300kHz
25℃	4.5	124.157	125.043	100kHz≤&≤300kHz
40℃	5.5	124.158	125.039	100kHz≤&≤300kHz
40 0	5.5	124.162	125.039	100kHz≤&≤300kHz
OFR		0.886kHz		
Results			ASS	

Test Mode: Mode 3

Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Lowest Frequency(K Hz)	Highest Frequency (KHz)	Limit
-10°C	5.0	127.359	128.243	100kHz≤&≤300kHz
-10 C	4.5	127.357	128.243	100kHz≤&≤300kHz
25℃	4.5	127.356	128.245	100kHz≤&≤300kHz
45℃	5.5	127.360	128.244	100kHz≤&≤300kHz
45 C	5.5	127.359	128.244	100kHz≤&≤300kHz
OFR		0.889kHz		
Result	S		P.	ASS



Page 14 of 31

Test Mode: Mode 4

Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Lowest Frequency(K Hz)	Highest Frequency (KHz)	Limit
-10℃	5.0	128.121	134.278	100kHz≤&≤300kHz
-10 C	4.5	128.121	134.280	100kHz≤&≤300kHz
25℃	4.5	128.120	134.282	100kHz≤&≤300kHz
45℃	5.5	128.123	134.278	100kHz≤&≤300kHz
45 (5.5	128.121	134.282	100kHz≤&≤300kHz
OFR		6.163kHz		
Results		PASS		

NOTE: All the modes had been tested, but only the worst data recorded in the report.




Page 15 of 31

5.3 TRANSMITTER OUT OF BAND (OOB) EMISSIONS

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Feb. 01, 2024	Jan. 31, 2025
Power amplifer	AR	75A250	18464	N/A	N/A
Active loop antenna(9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 05, 2024	Mar. 04, 2026

TEST SETUP:



TEST PROCEDURE:

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by normal signal,
- 3).Set SPA Center Frequency = fundamental frequency, RBW=VBW=200Hz, Span=5KHz, Detector=RMS. The 99 % OBW function shall be used to determine the operating frequency range, fH is the frequency of the upper marker resulting from the OFR, fL is the frequency of the lower marker resulting from the OFR.
- 4), Both normal test condition and extreme test condition applied



LIMITS

The OOB limits are visualized in figures; they are descending from the intentional limits from Table 3 at fH/fL with 10 dB/decade.




Figure 4: Out of band and spurious domain of a single frequency WPT system



Report No.: AGC05443240513ER02 Page 17 of 31

TEST RESULT Test Mode: Mode 1

Frequency range (KHz)		Frequency range (KHz) Maximum level @10m (dBuA/m)		Result
fSL -fL	122.385 to 124.157	Less than -22.52	See figure 4	Pass
fL	124.157	-22.52	65.80	Pass
fH	125.043	-23.04	65.80	Pass
fH - fSH	125.043 to 126.815	Less than -23.04	See figure 4	Pass

Test Mode: Mode 3

- Francis	oney renge (KU=)	Maximum level @10m	Limit @ 10m	Decult
Frequency range (KHz)		(dBuA/m)	(dBuA/m)	Result
fSL-fL	125.578 to 127.356	Less than -0.26	See figure 4	Pass
fL	127.356	-0.26	65.69	Pass
fH	128.245	-0.78	65.69	Pass
	128.245 to 130.023	Less than	See figure 4	
fH-fSH	123.2 13 10 100.020	-0.779999999999999	235 figure 1	Pass

Test Mode: Mode 4

Freque	Frequency range (KHz)		Limit @ 10m (dBuA/m)	Result
fSL-fL	126.198 to 128.12	Less than -12.71	See figure 5	Pass
fL	128.120	-12.71	65.65	Pass
fH	134.282	-25.04	65.65	Pass
fH-fSH	134.282 to 136.21	Less than -25.04	See figure 5	Pass

NOTE: All the modes had been tested, but only the worst data recorded in the report.



Page 18 of 31


5.4 TRANSMITTER SPURIOUS EMISSIONS

MEASUREMENT EQUIPMENT USED:


NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Feb. 01, 2024	Jan. 31, 2025
Power amplifer	AR	75A250	18464	N/A	N/A
Active loop antenna(9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 05, 2024	Mar. 04, 2026
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 05, 2023	Jan. 04, 2025

TEST SETUP:

FREQUENCY RANGE (9KHZ-30MHZ)



FREQUENCY RANGE (ABOVE 30MHZ)




Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Page 19 of 31

SUBSTITUTION METHOD:

RADIATED BELOW 1GHZ



TEST PROCEDURE:

For test method of frequency range (9kHz-30MHz)

The EUT was placed on the top of an insulating table 1.5 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

The H-field is measured with a shielded loop antenna connected to a measurement receiver.

The measuring bandwidth and detector type of the measurement receiver shall be in accordance with EN 300 330 Table 1.

For test method of frequency range (30 MHz-1000MHz)

EUT was placed on a 1.5m height wooden table. The search antenna is placed at 3m distances from the EUT and search antenna height is from 1-4m. With the transmitter operating at continuously mode, the turntable was slowly rotated to locate the direction of maximum emission. Once maximum direction is determined, the search antenna was raised and lowered in both vertical and horizontal polarizations.

The EUT was removed from the turntable and replaced with a linearly polarized antenna connected to a calibrated RF signal generator. The RF generator was set to a measured emission frequency and the search antenna was raised and lowered to produce a maximum received reading. The generator output was increased to match the radiated emission reading measured previously, and the result expressed in dB EIRP or ERP, correcting for substitution antenna gain at each frequency.



Page 20 of 31

LIMITS OF RADIATED DISTURBANCES

Below 30MHz

Table 4

State (see note)	Frequency 9 kHz ≤ f < 10 MHz	Frequency 10 MHz ≤ f < 30 MHz	
Operating	27 dBμA/m at 9 kHz descending 10 dB/dec	-3,5 dBμA/m	
Standby	5,5 dBμA/m at 9 kHz descending 10 dB/dec	-25 dBμA/m	
	g" means mode 2, 3 and 4 according to To to Table 2.	able 2; "standby" means mode 1	

ABOVE 30MHz

Table 5

State (see note)	47 MHz to 74 MHz 87,5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 790 MHz	Other frequencies between 30 MHz to 1 000 MHz
Operating	4 nW	250 nW
Standby	2 nW	2 nW
NOTE: "Operating" means	mode 2, 3 and 4 according to Table 2;	; "standby" means mode 1 according to
Table 2.		



Page 21 of 31

TEST LIMITS & RESULT

Test Mode: Mode 3

FREQUENCY RANGE (9KHZ-30MHZ)

	Operation Mode											
Frequency	Reading level	Total Factor	Emission level	Limit	Margin							
(MHz)	(dB µA)	(dB/m)	(dB μA/m)	(dBµA/m)	(dBµA/m)							
0.030	-7.75	-7.96	-15.71	21.76	37.47							
0.277	-11.08	-7.96	-19.04	12.12	31.16							
0.491	-12.51	-7.96	-20.47	9.63	30.11							
1.925	-14.43	-3.98	-18.41	3.70	22.11							
2.300	-13.45	-3.09	-16.54	2.93	19.47							
3.885	-12.41	-1.25	-13.66	0.65	14.31							

Remark:

(1) Corrected Power (dBm)= Total Factor + Reading Level

(2) Measuring frequencies from 9KHz to the 30MHz.

Data of measurement within this frequency range shown " -- " in the table above means the

reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Page 22 of 31

FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
84.59	32.24	V	-61.96	0.04	0.54	-61.46	-36.00	25.46
159.27	27.24	V	-67.85	0.06	1.10	-66.81	-36.00	30.81
357.25	30.65	V	-69.45	0.25	6.41	-63.29	-36.00	27.29
425.28	26.16	V	-74.14	0.33	7.00	-67.47	-36.00	31.47
628.91	28.76	V	-71.76	0.51	7.22	-65.05	-54.00	11.05
758.20	29.00	V	-70.92	0.61	6.50	-65.03	-36.00	29.03
91.24	30.96	Н	-63.61	0.04	1.48	-62.17	-54.00	8.17
156.35	27.43	Н	-66.83	0.06	0.80	-66.09	-36.00	30.09
353.48	29.94	Н	-68.23	0.25	5.89	-62.59	-36.00	26.59
434.35	26.44	Н	-72.12	0.34	6.62	-65.84	-36.00	29.84
628.68	29.65	Н	-69.66	0.51	7.22	-62.96	-54.00	8.96
727.21	28.95	Н	-70.19	0.59	6.65	-64.12	-36.00	28.12

Note: 1.The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Page 23 of 31

Test Mode: Mode 4(The low channel is the worst case) FREQUENCY RANGE (9KHZ-30MHZ)

	Operation Mode										
Frequency	Reading level	Total Factor	Emission level	Limit	Margin						
(MHz)	(dB µA)	(dB/m)	(dB μA/m)	(dBµA/m)	(dBµA/m)						
0.049	-7.72	-7.96	-15.68	19.62	35.30						
0.232	-11.08	-7.96	-19.04	12.90	31.94						
0.822	-12.80	-7.96	-20.76	7.39	28.16						
1.941	-14.34	-3.98	-18.32	3.66	21.98						
2.848	-13.33	-3.09	-16.42	2.00	18.41						
4.439	-12.82	-1.25	-14.07	0.07	14.14						

Remark:

- (1) Corrected Power (dBm) = Total Factor + Reading Level
- (2) Measuring frequencies from 9KHz to the 30MHz.
- Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Page 24 of 31

FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
87.91	32.78	V	-62.00	0.04	0.98	-61.06	-36.00	25.06
157.44	27.06	V	-66.25	0.06	0.90	-65.41	-36.00	29.41
356.22	30.65	V	-68.20	0.25	6.28	-62.18	-36.00	26.18
428.59	27.76	V	-72.26	0.34	6.94	-65.66	-36.00	29.66
627.64	28.53	V	-71.49	0.51	7.18	-64.82	-54.00	10.82
759.90	27.99	V	-70.41	0.61	6.55	-64.47	-36.00	28.47
95.36	30.17	Н	-64.82	0.04	1.80	-63.06	-54.00	9.06
154.04	26.80	Н	-67.76	0.06	0.70	-67.12	-36.00	31.12
350.07	28.38	Н	-70.08	0.25	5.50	-64.82	-36.00	28.82
432.11	27.76	Н	-71.70	0.34	6.76	-65.28	-36.00	29.28
629.11	29.08	Н	-71.38	0.51	7.26	-64.64	-54.00	10.64
728.95	28.96	Н	-70.46	0.59	6.70	-64.34	-36.00	28.34

Note: 1.The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Page 25 of 31

Test Mode: Mode 1

FREQUENCY RANGE (9KHZ-30MHZ)

	Standby Mode											
Frequency	Reading level	Total Factor	Emission level	Limit	Margin							
(MHz)	(dB µA)	(dB/m)	(dB μA/m)	(dBµA/m)	(dBµA/m)							
0.020	-7.50	-7.96	-15.46	1.97	17.42							
0.303	-10.38	-7.96	-18.34	-9.77	8.57							
0.440	-11.16	-7.96	-19.12	-11.39	7.73							
1.847	-23.09	-3.98	-27.07	-17.62	9.44							
4.023	-27.80	-3.09	-30.89	-21.00	9.89							
5.386	-26.75	-1.25	-28.00	-22.27	5.73							

Remark:

- (1) Corrected Power (dBm) = Total Factor + Reading Level
- (2) Measuring frequencies from 9KHz to the 30MHz.

Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Page 26 of 31

FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
94.25	27.42	V	-66.90	0.04	1.72	-65.22	-57.00	8.22
156.35	29.47	V	-64.54	0.06	0.80	-63.80	-57.00	6.80
358.38	28.78	V	-70.81	0.25	6.54	-64.52	-57.00	7.52
534.92	26.06	V	-74.47	0.44	6.84	-68.07	-57.00	11.07
677.99	30.94	V	-68.47	0.55	6.52	-62.49	-57.00	5.49
833.42	30.95	V	-68.04	0.66	6.51	-62.19	-57.00	5.19
132.48	27.45	Н	-65.22	0.05	0.06	-65.21	-57.00	8.21
161.55	28.86	Н	-64.68	0.06	1.28	-63.46	-57.00	6.46
342.73	29.03	Н	-68.83	0.24	5.66	-63.40	-57.00	6.40
539.04	27.50	Н	-71.75	0.45	7.14	-65.06	-57.00	8.06
676.92	28.61	Н	-69.63	0.55	6.56	-63.62	-57.00	6.62
830.23	27.36	Н	-72.40	0.66	6.30	-66.76	-57.00	9.76

Note: 1.The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.




Page 27 of 31

5.5 RECEIVER BLOCKING

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
MXG X-Series Vector Signal Generator	Agilent	N5182B	MY53050647	Feb. 01, 2024	Jan. 31, 2025
Active loop antenna(9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 05, 2024	Mar. 04, 2026
Clamp meter	PROVA	PROVA-11	17200101	Sep. 11, 2023	Sep. 10, 2024

TEST SETUP:



TEST PROCEDURE:

- 1). The test shall be carried out inside a test chamber according to clauses C.1.1 and C.1.2 in ETSI EN 300 330
- 2). A test loop with a radius r shall be used to create the magnetic field; the test loop shall lie on a non-metallic ground and the minimum distance to metallic objects (e.g. ground plane) shall be 0,75 m.The EUT shall be placed to the centre of the test-loop
- 3). The test loop shall be sufficiently large so that the test loop itself does not influence the WPT system; The radius R of the test-loop shall be in minimum $\Delta R = 0.75$ m larger than the maximum dimension r of the EUT.

$$R >= r + \Delta R$$
.

The maximum H-Field can be calculated from the loop current I (into the test-loop) with the following formula:

H=I/2R



Page 28 of 31

4)The required output current to achieve the required magnetic field at the WPT system shall be generated with a signal generator (unmodulated signal) at the test frequencies. For each test frequency the "reaction" of the device shall be recorded and checked against the performance criterion

LIMITS

The EUT shall achieve the wanted performance criterion, in the presence of the blocking signal.

Table 6: Receiver blocking limits

5	In-band signal	OOB signal	Remote-band signal
Frequency	Centre frequency (f _c) of the WPT	$f = f_c \pm F$ (see note)	$f = f_c \pm 10 \times F$ (see note)
	system (see clause 4.3.3)	873	253
Signal level field strength at	72 dBµA/m	72 dBµA/m	82 dBµA/m
the EUT	2 000 000 000 000 000 000 000 000 000 0	0.000 VEX.000 12 •0.000 VEX.000 VE	
NOTE: F = OFR see claus	e 4.3.3.		•

TEST RESULT

Test Mode: Mode 1

Test F	Frequency(KHz)	Signal level @ EUT	Performance	Result
In-band signal	124.600	72dBuA/m	No function loss	Pass
OOB signal	123.714	72dBuA/m	No function loss	Pass
oob algilia.	125.486	72dBuA/m	No function loss	Pass
Remote-band	115.740	82dBuA/m	No function loss	Pass
signal	133.460	82dBuA/m	No function loss	Pass

Test Mode: Mode 3

Test Frequency(KHz)		Signal level @ EUT	Performance	Result
In-band signal 127.800		72dBuA/m	No function loss	Pass
OOB signal	126.911	72dBuA/m	No function loss	Pass
	128.689	72dBuA/m	No function loss	Pass
Remote-band signal	118.910	82dBuA/m	No function loss	Pass
	136.690	82dBuA/m	No function loss	Pass




Page 29 of 31

6. INTERPRETATION OF MEASUREMENT RESULTS

All the measurement equipments and accessories have been carefully selected to meet the maximum measurement uncertainty specified below:

RF Frequency	± 1 x 10 ⁻⁷
RF Power, Conducted	± 0.75dB
Maximum Frequency Deviation: _ Within 300Hz and 6KHz of Audio Frequency _ Within 6KHz and 25KHz of Audio Frequency	± 5% ± 3dB
Adjacent channel power	± 3dB
Conducted Emission of Transmitter, Valid Up to 12.75GHz	± 4dB
Conducted Emissions of Receivers	± 3dB
Radiated Emission of Transmitter, Valid Up to 12.75GHz	± 6dB

P.S. Uncertainty figures are valid to confidence level of 95% calculated according to the methods described in the ETSI TR 100 028.





APPENDIX I: PHOTOGRAPHS OF TEST SETUP







Page 31 of 31

APPENDIX II: PHOTOGRAPHS OF THE EUT

Refer to the Report No.: AGC05443240513AP01
----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.



Health Test Report

Report No.: AGC05443240513EH01

PRODUCT DESIGNATION: Magnetic Wireless charger

BRAND NAME : N/A

MODEL NAME : MO2389

APPLICANT: MID OCEAN BRANDS B.V

DATE OF ISSUE : Jun. 07, 2024

STANDARD(S) : EN IEC 62311:2020

EN 50665:2017

REPORT VERSION: V1.0

Attestation of Global Confine (Shenzhen) Co., Ltd.



Page 2 of 13

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	1	Jun. 07, 2024	Valid	Initial release



Page 3 of 13

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
2. TECHNICAL INFORMATION	5
3. RF EXPOSURE MEASUREMENT	
3.1 INTRODUCTION	6
3.2 TEST LIMIT	7
3.3 EVALUATION METHODS	8
4. TEST EQUIPMENT LIST	9
5. EUT OPERATION CONDITION	9
4. TEST RESULT	10
5. CONCLUSION	10
APPENDIX I: PHOTOGRAPHS OF TEST SETUP	11



Page 4 of 13

1. GENERAL INFORMATION

Applicant	MID OCEAN BRANDS B.V	
Address	Unit 201 2/F,.Laford Centre, 838 Lai Chi Kok Road, Cheung Sha Wan, Kowloon, Hongkong	
Manufacturer	MID OCEAN BRANDS B.V	
Address	Unit 201 2/F,.Laford Centre, 838 Lai Chi Kok Road, Cheung Sha Wan, Kowloon, Hongkong	
Factory	MID OCEAN BRANDS B.V	
Address	Unit 201 2/F,.Laford Centre, 838 Lai Chi Kok Road, Cheung Sha Wan, Kowloon, Hongkong	
Product Designation	Magnetic Wireless charger	
Brand Name	N/A	
Test Model	MO2389	
Series Model	N/A	
Difference Description	N/A	
Date of receipt of test item	May 14, 2024	
Date of test	May 14, 2024 to Jun. 06, 2024	
Test Result	Pass	

Note: The test results of this report relate only to the tested sample identified in this report.

Reviewed By

Cici Li
(Project Engineer)

Calvin Liu
(Reviewer)

Max Zhang
Authorized Officer

Jun. 07, 2024

Jun. 07, 2024



Page 5 of 13

2. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

Product Designation	Magnetic Wireless charger
Brand Name	N/A
Test Model	MO2389
Hardware Version	V1.0
Software Version	V1.0
Operation Frequency	100KHz-205KHz
Modulation type	ASK
Antenna Type	Coil Antenna
EUT Input& Output Rating	Input: DC 5V/2A, 9V/1.67V, 12V/1.5A Output: DC 5V/1A, 9V/1.1A, 9V/1.67A
Wireless Charging Output Power	5W/10W/15W (Max 15W)

Note: For more details, please refer to the user's manual of the EUT.



Page 6 of 13

3. RF EXPOSURE MEASUREMENT

3.1 INTRODUCTION

This International Standard applies to electronic and electrical equipment for which no dedicated product- or product family standard regarding human exposure to electromagnetic fields applies.

This generic standard applies to electronic and electrical apparatus for which no dedicated product- or product family standard regarding human exposure to electromagnetic fields applies.

The frequency range covered is 0 Hz to 300 GHz.

The object of this generic standard is to provide assessment methods and criteria to evaluate such equipment against basic restrictions or reference levels on exposure of the general public related to electric, magnetic, electromagnetic fields and induced and contact current.

NOTE: This standard is intended to cover both intentional and non-intentional radiators. If the equipment complies with the requirements in another relevant standard, e.g. EN 62479 covering low power equipment, then the requirements of this standard (IEC 62311) are considered to be met and the application of this standard to that equipment is not necessary.



Page 7 of 13

3.2 TEST LIMIT

According to EN 62311:2008, Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz).

Annex F Measurement of E and H field

A commonly used probe size is 100 cm², also the contribution of the three axes X, Y and Z can be evaluated separately.

Reference levels for electric, magnetic and electromagnetic fields (0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density S _{eq} (W/m²)
0-1 Hz	_	3,2 × 10 ⁴	4 × 10 ⁴	_
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^{4}/f^{2}$	2 <u>42</u> 7
8-25 Hz	10 000	4 000/f	5 000/f	_
0,025-0,8 kHz	250/f	4/f	5/f	_
0,8-3 kHz	250/f	5	6,25	_
3-150 kHz	87	5	6,25	0 <u>10</u> 0
0,15-1 MHz	87	0,73/f	0,92/f	(
1-10 MHz	87/f ^{1/2}	0,73/f	0,92/f	_
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	1,375 f ^{1/2}	0,0037 f ^{1/2}	0,0046 f ^{1/2}	f/200
2-300 GHz	61	0,16	0,20	10




Page 8 of 13

3.3 EVALUATION METHODS

Measurement of E and H field

A commonly used probe size is 100 cm², also the contribution of the three axes X, Y and Z can be evaluated separately.



Note: Position A: Front of EUT; Position B: Left of EUT; Position C: back of EUT; Position D: Right of EUT; Position E: Top of EUT

Based on the above standard limit, any device with output power below 5A/m cannot produce an exposure exceeding this restriction under the most pessimistic exposure conditions.



Page 9 of 13

4. TEST EQUIPMENT LIST

Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Broadband Field	Narda Safety Test	ELT-400	J-0004	Jun. 07, 2023	Jun. 06, 2024
Meter	Solutions GmbH	EL1-400 J-0004	Juli. 07 , 2023	Juli. 00, 2024	
Drobo EUD	Narda Safety Test	2200/00 10	1.0045	Jun. 07, 2023	Jun. 06, 2024
Probe FHP	Solutions GmbH	2300/90.10	J-0015	Juli. 07, 2023	Juli. 00, 2024

5. EUT OPERATION CONDITION

NO.	TEST MODE DESCRIPTION		
1	Full Load mode		
2	Half Load mode		
3	Null Load mode		

Note:

1. The Mode 1 was the worst case and only the data of the worst case record in this report.



Page 10 of 13

4. TEST RESULT

Frequency	Maximum Radiated H-Field at 20cm		Limit	Result
MHz	A/m		A/m	Pass/Fail
	position E	0.062		
	position A	0.042		
127.8kHz	position B	0.035	5	Pass
	position C	0.037		
	position D	0.031		

Since Radiated H-Field at worse case is 0.062A/m which cannot exceed the exempt condition, 5A/m. It is deemed to full fit the requirement of RF exposure basic restriction specified in EC Council Recommendation (1999/519/EC).

5. CONCLUSION


Remark: EUT meets the basic requirements in the standard.




Page 11 of 13

APPENDIX I: PHOTOGRAPHS OF TEST SETUP






Position A






Page 12 of 13







Page 13 of 13



----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.